

INDUSTRIAL COMPONENT DATA

SACC-DSIV-M 8FS-3CON-L180-06 1524776 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSIV-M 8FS-3CON-L180-06



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSIV-M 8FS-3CON-L180-06
Catalog number	1524776
Category	Circular connector, mounting (PCB)
Minimum order	20 Pcs
Document ID	EO-F8BA880FCE
Generated	2026-07-27

Product Overview

Flush-type connector

Connect. plug. to be apar. wall poster., 3-pole, Female connection, straight, M8, coding: A, Rear mount, M8 x 1, Wave solder

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1524776

Packing unit 20 pc

Minimum order quantity 20 pc

Catalog page Page 230 (C-2-2013)

GTIN 4017918950101

Weight per Piece (excluding packing) 4.720 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C

Degree of protection IP67

General

Rated current at 40°C 4 A

Rated voltage 50 V AC

60 V DC

Number of positions 3

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M8 connector IEC 61076-2-104

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Solder pins

Mounting type Rear mounting M8 x 1 With locking nut

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Au

Contact carrier material PA 6.6

Material, knurls Nickel-plated brass

Sealing material NBR

Cable

Standards/specifications M8 connector IEC 61076-2-104

Standards and Regulations

Standard designation M8 connector

Standards/regulations IEC 61076-2-104

Flammability rating according to UL 94 HB

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 25;

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027140815eCl@ss 4.127140815eCl@ss 5.027143423eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss
7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 2.0EC001297ETIM 3.0EC002061ETIM 4.0EC002062ETIM 5.0EC002061...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSIV-M 8FS-3CON-L180-06 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.