

INDUSTRIAL COMPONENT DATA

SACCBP-M12FS-5CON-M16/0,5-PUR 1550151 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACCBP-M12FS-5CON-M16/0,5-PUR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACCBP-M12FS-5CON-M16/0,5-PUR
Catalog number	1550151
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-800739B1F0
Generated	2026-08-02

Product Overview

Flush-type connector

Conect. plug. to be apar. poster wall, 5-pole, PUR, greyish black RAL 7021, Rear wall mounting, M16 x 1.5 thread with flat nut, M16 x 1.5, Single stranded wires, cable length: 0.5 m, black halogen-free PUR, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1239979

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1550151

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356146395

Weight per Piece (excluding packing) 50.400 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 0.5 m

Ambient conditions

Degree of protection IP67

General

Rated current at 40°C 4 A

Rated voltage 60 V

Number of positions 5

Coding A - standard

Status display No

Overvoltage category II

Degree of pollution 3

Mounting type Rear mounting, M16 x 1.5 thread with flat nut M16 x 1.5

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material PA 6.6

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Cable

Cable type PUR halogen-free black

Cable abbreviation Li9Y-V1-C-V1-11Y

AWG signal line 22

Wire colors Brown, white, blue, black, gray

Overall twist 5 wires around filler to the core

Shielding Braided copper wires

Optical shield covering 85 %

External sheath, color black-gray RAL 7021

External cable diameter 5.90 mm

Cable weight 48 kg/km

Outer sheath, material PUR

Material, filler PE

Conductor material Bare Cu litz wires

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACCBP-M12FS-5CON-M16/0,5-PUR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.