

INDUSTRIAL COMPONENT DATA

SOL-SC-2ST-0-DC-1MPPT-1101UD 1140107 PHOENIX CONTACT String combiner box for photovoltaic systems up to 1000..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SOL-SC-2ST-0-DC-1MPPT-1101UD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SOL-SC-2ST-0-DC-1MPPT-1101UD
Catalog number	1140107
Category	Photovoltaic DC Stringbox
Minimum order	5 Pcs
Document ID	EO-0370CA190F
Generated	2026-08-04

Product Overview

String combiner box for photovoltaic systems up to 1000 V DC for connecting 1x 2 strings. String introduction from above. With surge protection, DC switch disconnecter, and SUNCLIX DC connector for the input and output sides.

String box for photovoltaic installations up to 1000 V DC for the connection of 1x 2 strings. Guiding the strings from above. With surge protection (type 1/2), DC charging disconnecter and SUNCLIX DC connector for the input and output side (SUNCLIX coupling connector included in the scope of delivery).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industry Solutions (IS)

Additional Product Information

Key Commercial Data

Orderkey 1140107

Packing unit 1

GTIN 4063151087883

Custom tariff number 85363030

Drawings

Safety equipment

General data

Ambient conditions

System parameter

Cable entry

Dimensions

Classifications

Drawings

Connection diagram

Schematic application drawing

Dimensional drawing

Housing dimensions

Circuit diagram

Connection of the remote indication contact on the surge protection

Schematic diagram

Connection of the PV strings

Schematic diagram

Connection to the inverter

Schematic diagram

Connection of the protective grounding conductor on the surge protection

[Back to top](#)System parameter

System voltage 1000 V DC (U_{max})

Number of string inputs 2

Current per string (max.) 16 A (I_{max})

Number of outputs 1

Number of supported MPP trackers 1

Switching capacity 32 A (1000 V)

[Back to top](#)Safety equipment

Surge protective device T1 / T2

Protection level U_p ≤ 3.5 kV

Total discharge current I_{total}(8/20) μs 40 kA

Total discharge current I_{total}(10/350) μs 5 kA

[Back to top](#)Cable entry

Type of cable entry SUNCLIX

Cable cross section string input 2.5 mm² ... 6 mm²

Cable cross section output 2.5 mm² ... 6 mm²

Cable cross section grounding 16 mm²

Sealing area grounding 6 mm ... 12 mm

[Back to top](#)General data

Material cover/door Polycarbonate (transparent)

Degree of protection IP65

Protection class II

[Back to top](#)Dimensions

Outer dimensions: width, height, depth 180 mm x 180 mm x 111 mm (Housing dimensions)

[Back to top](#)Ambient conditions

Ambient temperature (operation) -20 °C ... 45 °C....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SOL-SC-2ST-0-DC-1MPPT-1101UD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.