

INDUSTRIAL COMPONENT DATA

SOL-SC-2ST-0-DC-3MPPT-1001SE 1478915 PHOENIX CONTACT String box for photovoltaic installations up to 1000 V ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SOL-SC-2ST-0-DC-3MPPT-1001SE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SOL-SC-2ST-0-DC-3MPPT-1001SE
Catalog number	1478915
Category	Photovoltaic DC Stringbox
Minimum order	25 Pcs
Document ID	EO-35820C2A11
Generated	2026-08-05

Product Overview

String box for photovoltaic installations up to 1000 V DC for the connection of 3x 2 strings. With surge protection (type 1/2) and SUNCLIX DC connector for the input and output side (SUNCLIX coupling connector included in the scope of delivery). String combiner box for photovoltaic systems up to 1000 V DC for connecting 3x 2 strings. With surge protection (type 1/2) and SUNCLIX DC connectors for the input and output side (SUNCLIX mating connectors supplied as standard).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industry Solutions (IS)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type String combiner box (SCB)

Scope of delivery SUNCLIX DC connector for connecting the SCB

Insulation characteristics

Protection class II

Electrical propertiesGeneral

MPP voltage UN max. 1000 V DC

Non-load voltage UOC max. 1100 V DC

Current per string I_{max} max. 20 A

Total current MPP tracker max. 40 A

Surge protection

EN type T1
IEC test classification T1
Protection level Up ≤ 3.5 kV
Total discharge current Itotal(10/350) μs 5 kA
Total discharge current Itotal(8/20) μs 40 kA
Short-circuit current rating ISCPv 40 A
Input dataDC
Number of inputs: Strings 2 (per MPP tracker)
Number of supported MPP trackers 3
Output dataDC
Number of outputs: MPP tracker 3
Number of outputs: ± 1 (per MPP tracker)
Connection dataDC input
Type of cable entry SUNCLIX
Cable cross section 2.5 mm² ... 6 mm²
Protective bonding and protective grounding conductor
Type of cable entry Cable gland
Cable cross section 2x 16 mm²
External cable diameter 6 mm ... 12 mm
DC output
Type of cable entry SUNCLIX
Cable cross section 2.5 mm² ... 6 mm²
DimensionsHousing
Width 361 mm
Height 254 mm
Depth 111 mm
Material specificationsMaterial Housing Polycarbonate
Material Cover/door Polycarbonate (transparent)
Environmental and real-life conditionsAmbient conditions
Degree of protection IP65
Ambient temperature (operation) -20 °C ... 55 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SOL-SC-2ST-0-DC-3MPPT-1001SE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.