

INDUSTRIAL COMPONENT DATA

OV-24DC/350DC/1 2982634 PHOENIX CONTACT

Semi-conductor relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: OV-24DC/350DC/1



Manufacturer	PHOENIX CONTACT
MPN / Reference	OV-24DC/350DC/1
Catalog number	2982634
Category	Optocoupler
Minimum order	10 Pcs
Document ID	EO-17BBA5D8AB
Generated	2026-08-01

Product Overview

Semi-conductor relay

Solid-state relay, for signal amplification and galvanic separation of the control and load circuits, pluggable into plug-in sockets for soldering SIM-AMS, or with card connection for direct mounting on the printed circuit board, input: 4.25-32 V DC, output: 1-350 V DC/1 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2982634

Packing unit 10 pc

Catalog page Page 558 (C-7-2013)

GTIN 4046356131988

Weight per Piece (excluding packing) 23.000 g

Custom tariff number 85362010

Country of origin CN (China)

Dimensions

Width 10.5 mm

Height 43 mm

Depth 25.4 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 80 °C

Ambient temperature (storage/transport) -20 °C ... 80 °C

Input data

Nominal input voltage UN 24 V DC

Input voltage range 4.25 V DC ... 32 V DC

Switching threshold "0" signal, voltage < 1 V DC

Switching threshold "1" signal voltage > 3.3 V DC

Typical input current at UN 15 mA

Typical response time < 100 µs

Typical turn-off time < 250 µs

Transmission frequency 100 Hz

Output data

Output voltage range 1 V DC ... 350 V DC

Limiting continuous current 1 A (see derating curve)

Min. load current 1 mA

Leakage current 100 µA

Surge current 20 A (tp= 1 s)

Voltage drop at max. limiting continuous current 0.5 V

Output circuit 2-conductor

Type of protection Reverse polarity protection

Protective circuit/component Polarity protection diode

General

Test voltage input/output 4 kV (50 Hz, 1 min.)

Mounting position any

Assembly instructions Can be aligned with > 9 mm spacing

Operating mode 100% operating factor

Standards/regulations EN 61000-4-2

EN 61000-4-3

EN 61000-4-4

EN 55011

Standards and Regulations

Connection in acc. with standard CUL

Standards/regulations EN 61000-4-2

EN 61000-4-3

EN 61000-4-4

EN 55011

Insulation Basic insulation

Environmental Product Complianc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / OV-24DC/350DC/1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.