

INDUSTRIAL COMPONENT DATA

DP-STMED 6 3035690 PHOENIX CONTACT Spacer plate

Brand: PHOENIX CONTACT | Manufacturer Part Number: DP-STMED 6



Manufacturer	PHOENIX CONTACT
MPN / Reference	DP-STMED 6
Catalog number	3035690
Category	Endplate and partition plate for terminal block
Minimum order	50 Pcs
Document ID	EO-35E0030BE9
Generated	2026-08-03

Product Overview

Spacer plate

Spacer partition, length: 100.8 mm, width: 8.2 mm, colour: grey

Spacer plate, width: 8.2 mm, height: 100.8 mm, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Technical dataProduct propertiesProduct type Partition plate

Data management status

Article revision 01

Material specificationsColor gray (RAL 7042)

Flammability rating according to UL 94 V0

Insulating material group I

Insulating material PA

Static insulating material application in cold -60 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Dimensions Width 8.2 mm

Height 100.8 mm

Depth on NS 35/7,5 49.6 mm

Depth on NS 35/15 57.1 mm

Environmental and real-life conditions Ambient conditions

Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (operation) 20 % ... 90 %

Permis...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DP-STMED 6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.