

INDUSTRIAL COMPONENT DATA

SPE-T1-BH-M8MSM-STRM-90 1358333 PHOENIX CONTACT

Control cabinet feedthrough, protection index: IP20, number ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPE-T1-BH-M8MSM-STRM-90



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPE-T1-BH-M8MSM-STRM-90
Catalog number	1358333
Category	Fibre optic attenuator
Minimum order	1 Pcs
Document ID	EO-35E2B7EC48
Generated	2026-08-04

Product Overview

Control cabinet feedthrough, protection index: IP20, number of poles: 2, material: PA 6.6

Control cabinet feedthroughs

Control cabinet feed-through, degree of protection: IP20, number of positions: 2, material: PA 6.6

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

Additional Product Information

Technical dataProduct propertiesType SPE

Product type Data plug

Number of positions 2

Number of slots 2

Shielded yes

Insulation characteristics

Degree of pollution 2

Electrical propertiesRated voltage (II/2) 72 V

Rated surge voltage 2250 V DC

1000 V DC

Contact resistance < 20 m?

Transmission characteristics (category) CAT B

Transmission speed 1 Gbps

Power transmission PoDL

Output dataTransmission frequency 600.00 MHz

DimensionsWidth 18.6 mm

Height 31.8 mm

Length 34.25 mm

Material specificationsColor of the housing part black

Flammability rating according to UL 94 V0

Contact material Cu alloy

Contact surface material Au/Ni

Housing material PA 6.6

Cable/lineTest voltage Core/Core 1000 V DC

Test voltage Core/Shield 2250 V DC

Halogen-free yes

Flame resistance yes

Mechanical propertiesMechanical data

Insertion/withdrawal cycles > 750

Insertion force per signal contact < 30.00 N (in accordance with IEC 63171)

Extraction force per signal contact < 30 N (in accordance with IEC 63171)

Environmental and real-life conditionsAmbient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 85 °C

Standards and regulationsFlame resistance yes

MountingMounting type Screw thread

ETIM for 1358333 Connectors (EC002641)

Feature Name

Feature Value

Length (EF001438)

34.25 mm

Height (EF000040)

31.8 mm

Width (EF000008)

18.6 mm

Housing material (EF001596)

Other

Mounting method (EF000003)

Other

Degree of protection (IP), mounted (EF007466)

IP20

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPE-T1-BH-M8MSM-STRM-90 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.