

INDUSTRIAL COMPONENT DATA

SPE-T1-M12FS/ 2,0-97B/M12FS 1364631 PHOENIX CONTACT

Network cable, Single Pair Ethernet CAT A (10 MBit/s), 2..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPE-T1-M12FS/ 2,0-97B/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPE-T1-M12FS/ 2,0-97B/M12FS
Catalog number	1364631
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-85AE509EF7
Generated	2026-08-03

Product Overview

Network cable, Single Pair Ethernet CAT A (10 MBit/s), 2-pole, PVC, black, shielded (Advanced Shielding Technology), Straight female M12-SPE / IP67, to Straight female M12-SPE / IP67, cable length: 2 m

Network cable, Single Pair Ethernet CAT A (10 Mbps), 2-position, shielded (Advanced Shielding Technology), Socket straight M12-SPE / IP67, on Socket straight M12-SPE / IP67, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled

Sensor type Single Pair Ethernet

Number of positions 2

Application Standard

No. of cable outlets 1

Shielded yes

Insulation characteristics

Overvoltage category I

InterfacesBus system Ethernet

Signal type/category Single Pair Ethernet CAT A (ISO/IEC 63171), 10 Mbps

SignalingStatus display No

Status display present No

Electrical propertiesNominal voltage UN 72 V DC
Transmission medium Copper
Material specificationsFlammability rating according to UL 94 V0
ConnectorConnection 1
Type Socket straight M12-SPE / IP67
Shielded yes
Insertion/withdrawal cycles ≤ 100
Degree of protection IP67
Ambient temperature (operation) -25 °C ... 85 °C
Connection 2
Type Socket straight M12-SPE / IP67
Shielded yes
Handle color black
Material CuSn (Contact)
Ni/Au (Contact surface)
PP (Contact carriers)
TPU, hardly inflammable, self-extinguishing (Grip)
Zinc die-cast, nickel-plated (Screw connection)
FKM (Seal)
Insertion/withdrawal cycles ≤ 100
Degree of protection IP67
Ambient temperature (operation) -25 °C ... 85 °C
Cable/lineCable length 2 m
Single Pair Ethernet PUR flexible, black [97B]
Dimensional drawing
UL AWM Style 2095 (80°C/300 V)
Number of positions 2
Shielded yes
Cable type Single Pair Ethernet PUR flexible, black [97B]
Conductor structure 1 x 2 x AWG 22/7, S/FTP
Conductor structure signal line 7x
AWG signal line 22
Conductor cross section 2x 0.34 mm²
Wire diameter incl. insulation 1.65 mm
External cable diameter 5.1 mm....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPE-T1-M12FS/ 2,0-97B/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.