

INDUSTRIAL COMPONENT DATA

SPE-T1-M12MS/ 2,0-97B/M12FS 1364626 PHOENIX CONTACT

Network cable, Single Pair Ethernet CAT A (10 MBit/s), 2..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPE-T1-M12MS/ 2,0-97B/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPE-T1-M12MS/ 2,0-97B/M12FS
Catalog number	1364626
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-45D510230E
Generated	2026-08-03

Product Overview

Network cable, Single Pair Ethernet CAT A (10 MBit/s), 2-pole, PVC, black, shielded (Advanced Shielding Technology), Straight connector M12-SPE / IP67, to Straight female M12-SPE / IP67, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataItem PropertiesProduct Type Ready-made data cable
Sensor Type Single Pair Ethernet
Number of poles 2
application Standard
Number of Cable Outlets 1
Shielded Yes
Insulation Properties
Surge Category I
InterfacesBus system Ethernet
Signal Type/Category Single Pair Ethernet CAT A (ISO/IEC 63171), 10 MBit/s
SignageStatus Indication No
Available Status Indication No
Electrical PropertiesNominal voltage UN 72 V DC
Transmission Medium copper

Material DataFlammability class according to UL 94 V0

ConnectorsConnection 1

Construction M12-SPE / IP67 Straight Connector

Shielded Yes

Plug Cycles ≤ 100

Protection Index IP67

Ambient Temperature (Service) -25 °C ... 85 °C

Connection 2

Construction Straight Female M12-SPE / IP67

Shielded Yes

Grip body color black

Material CuSn (Contact)

Ni/Au (Surface Contacts)

PP (Contact Support)

TPU, low flammable, self-extinguishing (Grip body)

Zinc die-casting, nickel-plated (Screw connection)

FKM (Board)

Plug Cycles ≤ 100

Protection Index IP67

Ambient Temperature (Service) -25 °C ... 85 °C

Cable/LineCable length 2 m

Single Pair Ethernet Flexible PVC Black [97B]

Dimension Scheme

UL AWM Style 2095 (80°C/300V)

Number of poles 2

Shielded Yes

Cable type Single Pair Ethernet Flexible PVC Black [97B]

Conductor Design 1 x 2 x AWG 22/7, S/FTP

Conductor Construction Signal Cable 7x

AWG Signal Line 22

Line Section 2x 0.34 mm²

Conductor diameter incl. insulation 1.65 mm

Cable Outer Diameter 5.1 mm ± 0.2 mm

Outer Wrap, Material PVC

Outer Wrap, Color black...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPE-T1-M12MS/ 2,0-97B/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.