

INDUSTRIAL COMPONENT DATA

AXL F CNT2 INC2 1F 2688093 PHOENIX CONTACT Special function module

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL F CNT2 INC2 1F



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL F CNT2 INC2 1F
Catalog number	2688093
Category	Fieldbus, decentr. periphery - function-/technology module
Minimum order	1 Pcs
Document ID	EO-8C1D5CC5E8
Generated	2026-07-31

Product Overview

Special function module

AxiolineF, Function module, Counter input for 24 V signals:2, Transmitter inputs of incremental value:2, Symmetrical and asymmetric transmitters, Digital inputs:8, 24 VDC, Digital outputs:2, 24 VDC, transmission speed on the local bus:100 MBit/s, protection index:IP20, including bus socket module and AxiolineF connectors

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O
--------------	-----------------------

Additional Product Information

Key Commercial Data

Orderkey 2688093

Packing unit 1 pc

Catalog page Page 121 (C-6-2017)

GTIN 4046356501439

Weight per Piece (excluding packing) 255.000 g

Custom tariff number 85389091

Country of origin DE (Germany)

Dimensions

Dimensional drawing

Width 53.6 mm

Height 126.1 mm

Depth 54 mm

Note on dimensions The depth is valid when a TH 35-7,5 DIN rail is used (according to EN 60715).

Ambient conditions

Ambient temperature (operation) -25 °C ... 60 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP20

General

Mounting type DIN rail

Net weight 255 g

Note on weight specifications with connectors and bus base module

Diagnostics messages Short-circuit / overload of the digital outputs Yes

Error at the symmetrical incremental encoder Yes

Interfaces

Designation Axioline F local bus

No. of channels 2

Connection method Bus base module

Transmission speed 100 Mbps

Axioline potentials

Designation Axioline F local bus supply (UBus)

Supply voltage 5 V DC (via bus base module)

Current consumption typ. 100 mA

max. 120 mA

Power consumption typ. 0.5 W

max. 0.6 W

Designation Supply voltage input UI

Supply voltage 24 V DC

Supply voltage range 19.2 V DC ... 30 V DC including all...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL F CNT2 INC2 1F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.