

INDUSTRIAL COMPONENT DATA

SPT 1,5/ 1-H-3,5 OG 1706704 PHOENIX CONTACT Terminal block for printed circuit board, rated current: 17.5 A,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT 1,5/ 1-H-3,5 OG



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT 1,5/ 1-H-3,5 OG
Catalog number	1706704
Category	Printed circuit board terminal
Minimum order	100 Pcs
Document ID	EO-04AEA09671
Generated	2026-08-05

Product Overview

Terminal block for printed circuit board, rated current: 17.5 A, rated voltage: 200 V, pitch: 3.5 mm, number of poles: 1, connection type: Push-in spring connection, mounting: Wave soldering, driver/printed circuit board connection direction: 0 °, color: orange

Terminal block for printed circuit board, nominal current: 17.5 A, dimensioning voltage (III/2): 200 V, nominal section: 1.5 mm², Number of potentials: 1, Number of rows: 1, Number of poles per row: 1, article family: SPT 1.5/.. -H, pitch: 3.5mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/printed circuit board connection direction: 0°, color: orange, Pin arrangement: Linear double pin arrangement, Pin length [P]: 2.5mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

PCB terminal block, nominal current: 17.5 A, nom. voltage: 200 V, pitch: 3.5 mm, number of positions: 1, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: orange
Your advantages

Time saving push-in connection, tools not required
Defined contact force ensures that contact remains stable over the long term
Clamping space opened by means of fixed screwdriver enables convenient conductor connection
Operation and conductor connection from one direction enable integration into front of device
Two solder pins reduce the mechanical strain on the soldering spots
Key Commercial Data

Orderkey 1706704

Packing unit 100 pc

Minimum order quantity 100 pc
Note Made to Order (non-returnable)
GTIN 4046356872195
Weight per Piece (excluding packing) 1.330 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Range of articles SPT 1,5/..-H
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/3) 160 V
Rated voltage (III/2) 200 V
Rated voltage (II/2) 400 V
Connection in acc. with standard EN-VDE
Nominal current IN 17.5 A
Nominal cross section 1.5 mm²
Solder pin surface Sn
Stripping length 10 mm
Number of positions 1
Connection data
Conductor cross section AWG min. 24
Conductor cross section AWG max. 16
Standards and Regulations
Connection in acc. with standard EN-VDE
Environmental Product Compliance
China RoHS Environmentally friendly use period: unl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT 1,5/ 1-H-3,5 OG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.