

INDUSTRIAL COMPONENT DATA

SPT 1,5/ 1-V-3,5 OG SWO 1706786 PHOENIX CONTACT

Terminal block for printed circuit board, rated current: 17...

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT 1,5/ 1-V-3,5 OG SWO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT 1,5/ 1-V-3,5 OG SWO
Catalog number	1706786
Category	Printed circuit board terminal
Minimum order	100 Pcs
Document ID	EO-4357510D83
Generated	2026-08-05

Product Overview

Terminal block for printed circuit board, rated current: 17.5 A, rated voltage: 200 V, pitch: 3.5 mm, number of poles: 1, connection type: Push-in spring connection, mounting: Wave soldering, conductor/printed circuit board connection direction: 90 °, color: orange

Terminal block for printed circuit board, nominal current: 17.5 A, dimensioning voltage (III/2): 200 V, nominal section: 1.5 mm², Number of potentials: 1, Number of rows: 1, Number of poles per row: 1, article family: SPT 1.5/.. -V, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 90 °, color: orange, Pin arrangement: Double linear pin arrangement, Pin length [P]: 2.5mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

PCB terminal block, nominal current: 17.5 A, nom. voltage: 200 V, pitch: 3.5 mm, number of positions: 1, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 90 °, color: orange
Your advantages

Time saving push-in connection, tools not requiredDefined contact force ensures that contact remains stable over the long termClamping space opened by means of fixed screwdriver enables convenient conductor connectionOperation and conductor connection from one direction enable integration into front of deviceTwo solder pins reduce the mechanical strain on the soldering spotsKey Commercial Data

Orderkey 1706786

Packing unit 1

GTIN 4046356894425

Custom tariff number 85369010

Electrical parameters

Rated current 17.5 A

Rated insulation voltage (III/2) 200 V

Rated surge voltage (III/2) 2.5 kV

Contact resistance 0.8 mΩ

Connection capacity

Conductor cross section solid 0.2 mm² ... 1.5 mm²

Conductor cross section flexible 0.2 mm² ... 1.5 mm²

Conductor cross section AWG / kcmil 24 ... 16

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm² (Stripping length 8 mm)

Stripping length 10 mm

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics hot-dip tin-plated

Metal surface terminal point (top layer) Tin (4 - 8 μm Sn)

Metal surface soldering area (top layer) Tin (4 - 8 μm Sn)

Material data - housing

H...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT 1,5/ 1-V-3,5 OG SWO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.