

INDUSTRIAL COMPONENT DATA

SPT 16/ 2-V-10,0-ZB MIX RD/ BU 1705568 PHOENIX CONTACT

Terminal block for printed circuit board, rated curre..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT 16/ 2-V-10,0-ZB MIX RD/ BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT 16/ 2-V-10,0-ZB MIX RD/ BU
Catalog number	1705568
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-5E43088B7D
Generated	2026-08-06

Product Overview

Terminal block for printed circuit board, rated current: 76 A, rated voltage: 1000 V, pitch: 10 mm, number of poles: 2, connection type: Push-in spring connection, mounting: Wave soldering, color: multicolor

Terminal block for printed circuit board, nominal current: 76 A, dimensioning voltage (III/2): 1000 V, nominal section: 16 mm², Number of potentials: 2, Number of rows: 1, Number of poles per row: 2, family of articles: SPT 16/.. -V, pitch: 10 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 90 °, color: multicolor, Pin arrangement: Zigzag Pins W, Pin length [P]: 4.1 mm, packaging type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

PCB terminal block, nominal current: 76 A, nom. voltage: 1000 V, pitch: 10 mm, number of positions: 2, connection method: Push-in spring connection, mounting: Wave soldering, color: multi-color

Your advantages

Time saving push-in connection, tools not required
Defined contact force ensures that contact remains stable over the long term
Clamping space opened by means of fixed screwdriver enables convenient conductor connection
Unrestricted

600-V-UL approval thanks to compact zig-zag pinning
Vertical connection enables multi-row arrangement on the PCB
Key

Commercial Data

Orderkey 1705568

Packing unit 1

GTIN 4046356773157

Custom tariff number 85369010

Electrical parameters

Rated current 76 A

Rated insulation voltage (III/2) 1000 V

Rated surge voltage (III/2) 8 kV

Connection capacity

Conductor cross section solid 0.75 mm² ... 16 mm²

Conductor cross section flexible 0.75 mm² ... 16 mm²

Conductor cross section AWG / kcmil 20 ... 4

Conductor cross section flexible, with ferrule without plastic sleeve 0.75 mm² ... 16 mm²

2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.75 mm² ... 4 mm²

Stripping length 18 mm

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics hot-dip tin-plated

Metal surface terminal point (top layer) Tin (10 - 16 µm Sn)

Metal surface soldering area (top layer) Tin (10 - 16 µm Sn)

Material data - housing

Housing color multi-c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT 16/ 2-V-10,0-ZB MIX RD/ BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.