

INDUSTRIAL COMPONENT DATA

CA-17P1N126L00 1624055 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: CA-17P1N126L00



Manufacturer	PHOENIX CONTACT
MPN / Reference	CA-17P1N126L00
Catalog number	1624055
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-810DC66CEA
Generated	2026-08-04

Product Overview

Device connector, front mounting

M23, Conect. plug. to be apar. front wall, AC, straight, shielded: yes, for standard lock and SPEEDCON, No. of poles: 17, Direction of rotation: Standard, type of contact: Male, Weld connection, Axial joint, Central fixing M20 x 1.5, positionable by lock nut, coding:N

M23, Device connector front mounting, series: CA, straight, shielded: yes, for standard and SPEEDCON interlock, No. of pos.: 17, Direction of rotation: Standard, contact connection type: Pin, Solder connection, Axial seal, Central fastening M20 x 1.5, can be positioned via a locking nut, coding: N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesProduct type Circular connectors (device side)

Data management status

Article revision 06

Material specificationsFlammability rating according to UL 94 V0

ConnectorInsulating body

Coding N

Insulation body material PBT

Contact material CuZn

Contact surface material Ni/Au

Insertion/withdrawal cycles 100
Connection method Solder connection
Contact switching type Pin
Application Signal
Number of positions 17
Direction of rotation Standard
Connection profile 17
Rated voltage 48 V AC
74 V DC
Rated surge voltage 1.5 kV
Overvoltage category III
Degree of pollution 3
Contact diameterSignal contacts 1 mm
Litz wire cross-sectionSignal contactsmax. 1 mm²
Nominal current per signal contact 8 A
Housing
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Type of locking for standard and SPEEDCON interlock
Pg screw connection none
Degree of protection (plugged in) IP67
Thread type M23
ETIM for 1624055 Connectors (EC003569)
Feature Name
Feature Value
With shield connection (EF002535)
No
With PE-connection (EF005600)
No
Inflammability class of insulation material according to UL94 (EF002521)
V0
With thread (EF003723)
Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CA-17P1N126L00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.