

INDUSTRIAL COMPONENT DATA

MVSTBR 2,5 HC/ 3-ST-5,08 GY 1711605 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MVSTBR 2,5 HC/ 3-ST-5,08 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	MVSTBR 2,5 HC/ 3-ST-5,08 GY
Catalog number	1711605
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-1342442906
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: gray, nominal current: 16 A (see derating curve), nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: MVSTBR 2.5 HC/.. -ST, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 90 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5 HC, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1711605

Packing unit 1

GTIN 4055626247861

Custom tariff number 85366990

Dimensions

Length [l] 12.5 mm

Width [w] 15.24 mm

Height [h] 26 mm

Pitch 5.08 mm

Dimension a 5.08 mm

General

Range of articles MVSTBR 2,5 HC/..-ST

Number of positions 3

Connection method Screw connection with tension sleeve

Insulating material group I

Rated voltage (III/2) 320 V

Nominal current I_N 16 A (see derating curve)

Nominal cross section 2.5 mm²

Flammability rating according to UL 94 V0

Screw thread M3

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309

ETIM 5.0EC002638ETIM 6.0EC002638

ETIM for 1711605 Connectors (EC002638)

Feature Name

Feature Value

Type of connection (EF000064)

Other

Contact type (EF001587)

Bus

Number of poles (EF001391)

3

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5.08 mm

Modular spacing connections (EF006827)

5.08 mm

Angle contact/conductor connection (EF007546)

Other

Rated current I_n (EF008250)

16 A

Rated voltage (EF000228)

320 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connectable conductor cross section fine-strand without cable end sleeve (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MVSTBR 2,5 HC/ 3-ST-5,08 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.