

INDUSTRIAL COMPONENT DATA

SPT 2,5/ 4-H-5,0-EX BD:14-11SO 1101810 PHOENIX CONTACT

Terminal for printed circuit board, rated current: 23..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT 2,5/ 4-H-5,0-EX BD:14-11SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT 2,5/ 4-H-5,0-EX BD:14-11SO
Catalog number	1101810
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-0F7E298D74
Generated	2026-08-03

Product Overview

Terminal for printed circuit board, rated current: 23 A, pitch: 5 mm, number of poles: 4, type of connection: spring clamp push-in, mounting: Soldering by wave direction for connection conductor/pcb: 0 °, color: green

Terminal block for printed circuit board, nominal current: 23 A, nominal section: 2.5 mm², number of rows: 1, number of poles per row: 4, article family: SPT 2.5/.. -H-EX, pitch: 5mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 0°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.5mm, number of solder pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT 2,5/ 4-H-5,0-EX BD:14-11SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.