

INDUSTRIAL COMPONENT DATA

SPT 5/ 4-H-7,5 MIX YE/GN 1076254 PHOENIX CONTACT PCB terminal block SPT 5/ 4-H-7,5 MIX YE/GN 1076254

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT 5/ 4-H-7,5 MIX YE/GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT 5/ 4-H-7,5 MIX YE/GN
Catalog number	1076254
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-880178734E
Generated	2026-08-05

Product Overview

PCB terminal block - SPT 5/ 4-H-7,5 MIX YE/GN - 1076254

Terminal block for printed circuit board, nominal current: 41 A, dimensioning voltage (III/2): 1000 V, nominal section: 6 mm², Number of potentials: 4, Number of rows: 1, Number of poles per row: 4, family of articles: SPT 5/.. -H, pitch: 7.5mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/printed circuit board connection direction: 0°, color: multicolor, Pin arrangement: Linear pin arrangement, Pin length [P]: 4.6mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

PCB terminal block, nominal current: 41 A, nom. voltage: 1000 V, pitch: 7.5 mm, number of positions: 4, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: multi-color

Key Commercial Data

Orderkey 1076254

Packing unit 1

GTIN 4055626783826

Custom tariff number 85369010

Item properties

Brief article description PCB terminal block

Range of articles SPT 5/..-H

Pitch 7.5 mm

Number of positions 4
Connection method Push-in spring connection
Mounting type Wave soldering
Pin layout Linear pinning
Number of levels 1
Number of connections 4
Number of potentials 4
Electrical parameters
Rated current 41 A
Rated insulation voltage (III/2) 1000 V
Rated surge voltage (III/2) 6 kV
Connection capacity
Conductor cross section solid 0.2 mm² ... 10 mm²
Conductor cross section flexible 0.2 mm² ... 6 mm²
Conductor cross section AWG / kcmil 24 ... 8
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 6 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 4 mm²
2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.25 mm² ... 1.5 mm²
Stripping length 15 mm
Material data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics Tin-plated
Metal surface terminal point (top layer) Tin (4 - 8 µm Sn)
Metal surface soldering area (top layer) Tin (4 - 8 µm....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT 5/ 4-H-7,5 MIX YE/GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.