


INDUSTRIAL COMPONENT DATA

SPT-THR 1,5/ 2-H-3,5 P26 R24 1128036 PHOENIX CONTACT

PCB terminal block, nominal current: 13.5 A, rated volt..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT-THR 1,5/ 2-H-3,5 P26 R24



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT-THR 1,5/ 2-H-3,5 P26 R24
Catalog number	1128036
Category	Printed circuit board terminal
Minimum order	250 Pcs
Document ID	EO-7AD1F2CCA9
Generated	2026-08-05

Product Overview

PCB terminal block, nominal current: 13.5 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², pitch: 3.5 mm, number of positions: 2, connection method: Push-in spring connection, mounting: THR soldering, conductor/PCB connection direction: 0 °, color: black, Pin layout: Linear double pinning, Solder pin [P]: 2.6 mm

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 160 V, nominal section: 1.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, family of articles: SPT 1.5/.. -H-THR, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Weld THR, conductor connection direction/printed circuit board: 0 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.6 mm, number of solder pins per potential: 2, packaging type: 24 mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1128036

Packing unit 1

GTIN 4063151055189

Custom tariff number 85369010

Drawings

Electrical parameters

Material data - contact

[Dimensions for the product](#)

[Packaging information](#)

[Ambient conditions](#)

[Pull-out test](#)

[Air clearances and creepage distances](#)

[Resistance to ageing, humidity and penetration of solids](#)

[Item properties](#)

[Connection capacity](#)

[Material data - housing](#)

[Dimensions for PCB design](#)

[General product information](#)

[Termination and connection method](#)

[Electrical tests](#)

[Vibration test](#)

[Classifications](#)

[Drawings](#)

[Diagram](#)

Type: SPT-THR 1,5/ 5-H-3,5(3,81) P26

Tested according to DIN EN 60512-5-2:2003-01

Reduction factor = 1

Number of positions: 5

[Back to topItem properties](#)

[Brief article description PCB terminal block](#)

Range of articles SPT 1,5/...-H-THR

Pitch 3.5 mm

Number of positions 2

Connection method Push-in spring connection

Mounting type THR soldering

Pin layout Linear double pinning

Number of levels 1

[Back to topElectrical parameters](#)

Nom. voltage 160 V

[Back to topConnection capacity](#)

Connection method Push-in spring connection

Conductor cross section solid 0.2 mm² ... 1.5 mm²

Conductor cross section flexible 0.2 mm² ... 1.5 mm²

Conductor cross section AWG / kcmil 24 ... 16

Conductor cross section flexible, with ferrule without plastic sleeve 0.2 mm² ... 1.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.2 mm² ... 0.75 mm²

Stripping length 8 mm

[Back to topMaterial data - contact](#)

Note WEEE/RoHS-compliant, free of whiskers accor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT-THR 1,5/ 2-H-3,5 P26 R24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.