

INDUSTRIAL COMPONENT DATA

SPT-THR 1,5/ 4-H-5,08 P26 R32 1739223 PHOENIX CONTACT

Printed circuit board terminal, rated current: 17.5 A,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT-THR 1,5/ 4-H-5,08 P26 R32



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT-THR 1,5/ 4-H-5,08 P26 R32
Catalog number	1739223
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-1F1DB828E2
Generated	2026-08-06

Product Overview

Printed circuit board terminal, rated current: 17.5 A, rated voltage (III/2): 320 V, rated cross-section: 1.5 mm², number of rows: 1, number of poles per row: 4, item family: SPT 1.5/.. -H-THR, pitch: 5.08 mm, connection type: Push-in spring connection, mounting: THR soldering/wave soldering, conductor connection direction/printed circuit board: 0°, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.6 mm, number of solder pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT-THR 1,5/ 4-H-5,08 P26 R32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.