

INDUSTRIAL COMPONENT DATA

SPT-THR 2,5/11-V-5,0 P20 R72 1135344 PHOENIX CONTACT

Printed circuit board terminal, rated current: 32 A, ra..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT-THR 2,5/11-V-5,0 P20 R72



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT-THR 2,5/11-V-5,0 P20 R72
Catalog number	1135344
Category	Printed circuit board terminal
Minimum order	125 Pcs
Document ID	EO-CA43D21D5D
Generated	2026-08-04

Product Overview

Printed circuit board terminal, rated current: 32 A, rated voltage (III/2): 400 V, rated cross-section: 4 mm², number of potentials: 11, number of rows: 1, number of poles per row: 11, item family: SPT 2.5/.. -V-THR, pitch: 5 mm, connection type: Push-in spring connection, mounting: THR soldering/wave soldering, conductor connection direction/printed circuit board: 90°, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 2 mm, number of solder pins per potential: 2, packaging type: 72 mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT-THR 2,5/11-V-5,0 P20 R72 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.