

INDUSTRIAL COMPONENT DATA

SPT-THR 2,5/ 8-V-5,0 P26 1135352 PHOENIX CONTACT

Printed circuit board terminal, nominal current: 32 A, nomi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT-THR 2,5/ 8-V-5,0 P26



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT-THR 2,5/ 8-V-5,0 P26
Catalog number	1135352
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-25013CB51F
Generated	2026-08-03

Product Overview

Printed circuit board terminal, nominal current: 32 A, nominal voltage (III/2): 400 V, nominal section: 4 mm², number of potentials: 8, number of rows: 1, number of poles per row: 8, article family: SPT 2.5/.. -V-THR, pitch: 5 mm, connection type: Push-in spring connection, mounting: THR soldering/wave soldering, conductor connection direction/printed circuit board: 90 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.6 mm, number of solder pins per potential: 2, packaging type: boxed

Printed circuit board terminal, rated current: 32 A, sizing voltage (III/2): 400 V, nominal section: 4 mm², number of potentials: 8, Number of rows: 1, Number of poles per row: 8, article family: SPT 2.5/.. -V-THR, pitch: 5 mm, connection type: Push-in spring connection, mounting: THR welding, connection direction conductor/printed circuit board: 0°, color: black, Pin arrangement: Double linear pin arrangement, Pin length [P]: 2.6 mm, packaging type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

ETIM for 1135352 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

21.75 mm

Number of electrical connections (EF008252)

8

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

5 mm

Rated current I_n (EF008250)

32 A

Rated voltage (EF000228)

400 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Spring clamp connection

Connectable conductor cross section solid-core (EF007337)

0.2 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section multi-wired (EF007343)

4 mm²

Connection type PCB (EF006822)

Soldering connection

Material connection surface (EF006826)

Tin

Diameter connection pin (EF006823)

1.2 mm

Length pin (EF006825)

2.6 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Black

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT-THR 2,5/ 8-V-5,0 P26 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.