

## INDUSTRIAL COMPONENT DATA

# SPTA 1/13-3,5 1704904 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTA 1/13-3,5



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | SPTA 1/13-3,5                  |
| Catalog number  | 1704904                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 50 Pcs                         |
| Document ID     | EO-04ECC6D293                  |
| Generated       | 2026-08-05                     |

## Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 9 A, nominal voltage (III/2): 200 V, nominal cross-section: 1 mm<sup>2</sup>, number of potentials: 13, number of rows: 1, number of poles per row: 13, article family: SPTA 1/, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 65 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of welding pins per potential: 1, packaging type: boxed

Printed circuit board terminal, nominal current: 9 A, rated voltage (III/2): 200 V, nominal cross section: 1 mm<sup>2</sup>, number of potentials: 13, number of rows: 1, number of positions per row: 13, product range: SPTA 1/, pitch: 3.5 mm, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 65 °, color: green, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm, number of solder pins per potential: 1, type of packaging: packed in cardboard

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family SPTA 1/

Product line COMBICON Terminals S

Number of positions 13

Pitch 3.5 mm

Number of connections 13  
Number of rows 1  
Number of potentials 13  
Pin layout Linear pinning  
Solder pins per potential 1  
Data management status  
Article revision 02  
Electrical propertiesNominal current  $I_N$  9 A  
Nominal voltage  $U_N$  200 V  
Rated voltage (III/3) 160 V  
Rated surge voltage (III/3) 2.5 kV  
Rated voltage (III/2) 200 V  
Rated surge voltage (III/2) 2.5 kV  
Rated voltage (II/2) 400 V  
Rated surge voltage (II/2) 2.5 kV  
Connection dataConnection technology  
Nominal cross section 1 mm<sup>2</sup>  
Conductor connection  
Connection method Push-in spring connection  
Conductor cross section rigid 0.2 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross section flexible 0.2 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross section AWG 24 ... 16  
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm<sup>2</sup> ... 0.75 mm<sup>2</sup>  
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm<sup>2</sup> ... 0.75 mm<sup>2</sup>  
Stripping length 8 mm  
MountingMounting type Wave soldering  
Pin layout Linear pinning  
Material specificationsMaterial data - contact  
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201  
Contact material Cu alloy  
Surface characteristics hot-dip tin-plated  
Metal surface terminal point (top layer) Tin (4 - 8 µm Sn)  
Metal surface soldering area (top layer) Tin (4 - 8 µm Sn)  
Material data - housing  
Color (Housing) green (6021)...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTA 1/13-3,5 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.