


INDUSTRIAL COMPONENT DATA

SPTA 1/ 4-5,0 BDWH:M1-M4 1502858 PHOENIX CONTACT PCB terminal, rated current: 9 A, rated voltage (III/2): 20..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTA 1/ 4-5,0 BDWH:M1-M4



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPTA 1/ 4-5,0 BDWH:M1-M4
Catalog number	1502858
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-5830279F14
Generated	2026-08-03

Product Overview

PCB terminal, rated current: 9 A, rated voltage (III/2): 200 V, rated cross-section: 1 mm², number of rows: 1, number of poles per row: 4, item family: SPTA 1/, pitch: 5 mm, connection type: Push-in spring connection, mounting: Wave soldering, connection direction conductor/printed circuit board: 65°, Color: Green, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 3.5mm, Number of Solder Pins by Potential: 1, Packing Type: Boxed Packaging

PCB terminal block, nominal current: 9 A, rated voltage (III/2): 200 V, nominal cross section: 1 mm², number of rows: 1, number of positions per row: 4, product range: SPTA 1/, pitch: 5 mm, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 65°, color: green, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm, number of solder pins per potential: 1, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct line COMBICON Terminals S

Product type Printed circuit board terminal

Product family SPTA 1/

Number of positions 4

Pitch 5 mm

Number of rows 1

Pin layout Linear pinning

Solder pins per potential 1

Electrical propertiesNominal current I_N 9 A

Nominal voltage U_N 200 V

Degree of pollution 3

Rated voltage (III/3) 160 V

Rated surge voltage (III/3) 2.5 kV

Rated voltage (III/2) 200 V

Rated surge voltage (III/2) 2.5 kV

Rated voltage (II/2) 400 V

Rated surge voltage (II/2) 2.5 kV

Connection dataConnection technology

Nominal cross section 1 mm²

Conductor connection

Connection method Push-in spring connection

Conductor cross section rigid 0.2 mm² ... 1.5 mm²

Conductor cross section flexible 0.2 mm² ... 1.5 mm²

Conductor cross section AWG 24 ... 16

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 0.75 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 0.75 mm²

Stripping length 8 mm

MountingMounting type Wave soldering

Pin layout Linear pinning

Material specificationsMaterial data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics hot-dip tin-plated

Metal surface terminal point (top layer) Tin (4 - 8 µm Sn)

Metal surface soldering area (top layer) Tin (4 - 8 µm Sn)

Material data - housing

Color (Housing) green (6021)

Insulating material PA

Insulating material group I

CTI according to IEC....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTA 1/ 4-5,0 BDWH:M1-M4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.