

INDUSTRIAL COMPONENT DATA

SPTA 1,5/12-5,08 BD:16-23 1050089 PHOENIX CONTACT

Terminal for printed circuit board, rated voltage: 320 V, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTA 1,5/12-5,08 BD:16-23



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPTA 1,5/12-5,08 BD:16-23
Catalog number	1050089
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-3565EAA6F7
Generated	2026-08-04

Product Overview

Terminal for printed circuit board, rated voltage: 320 V, pitch: 5,08 mm, number of poles: 12, connection type: spring clamp push-in, mounting: Soldering by wave, color: green

Terminal block for printed circuit board, nominal current: 9 A, dimensioning voltage (III/2): 320 V, nominal cross-section: 1.5 mm², Number of potentials: 12, Number of rows: 1, Number of poles per row: 12, article family: SPTA 1.5/, pitch: 5.08 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45°, color: green, Pin arrangement: Double linear pin arrangement, Pin length [P]: 3.4 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTA 1,5/12-5,08 BD:16-23 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.