


**INDUSTRIAL COMPONENT DATA**

# SPTA 1,5/ 5-3,81 BD:10-AM 1825403 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTA 1,5/ 5-3,81 BD:10-AM



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | SPTA 1,5/ 5-3,81 BD:10-AM      |
| Catalog number  | 1825403                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 100 Pcs                        |
| Document ID     | EO-C8A3464E15                  |
| Generated       | 2026-08-04                     |

## Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 9 A, nominal voltage (III/2): 160 V, nominal cross-section: 1.5 mm<sup>2</sup>, number of potentials: 5, number of rows: 1, number of poles per row: 5, article family: SPTA 1.5/, pitch: 3.81 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.4 mm, number of welding pins per potential: 2, packaging type: boxed

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1825403

Packing unit 1

GTIN 4046356804820

Custom tariff number 85369010

Item properties

Brief article description PCB terminal block

Range of articles SPTA 1,5/

Pitch 3.81 mm

Number of positions 5

Connection method Push-in spring connection  
Mounting type Wave soldering  
Pin layout Linear double pinning  
Number of levels 1  
Number of connections 5  
Number of potentials 5  
Electrical parameters  
Rated current 9 A  
Rated insulation voltage (III/2) 160 V  
Rated surge voltage (III/2) 2.5 kV  
Connection capacity  
Conductor cross section solid 0.2 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross section flexible 0.2 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross section AWG / kcmil 24 ... 16  
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Stripping length 10 mm  
Material data - contact  
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201  
Contact material Cu alloy  
Surface characteristics Tin-plated  
Metal surface terminal point (top layer) Tin (4 - 8 µm Sn)  
Metal surface soldering area (top layer) Tin (4 - 8 µm Sn)  
Material data - housing  
Insulating material PA  
Insulating material group I  
CTI according to IEC 60112 600  
Flammability rating according to UL 94 V0  
Glow wire flammability index GWFI according to EN 60695-2-12 850  
Glow wire ignition temperature GWIT according to EN 60695-2-13 775  
Temperature for the ball pressure test accord...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTA 1,5/ 5-3,81 BD:10-AM with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.