

INDUSTRIAL COMPONENT DATA

SPTA 16/10-CB-10,0ZM2RZBDL3INO 1183048 PHOENIX CONTACT Printed circuit board terminal, rated current: 76 A, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTA 16/10-CB-10,0ZM2RZBDL3INO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPTA 16/10-CB-10,0ZM2RZBDL3INO
Catalog number	1183048
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-7D5CF1F688
Generated	2026-08-06

Product Overview

Printed circuit board terminal, rated current: 76 A, rated voltage (III/2): 1000 V, rated cross-section: 16 mm², number of potentials: 10, number of rows: 1, number of poles per row: 10, item family: SPTA 16/, pitch: 10 mm, connection type: Push-in spring connection, mounting: Wave soldering, driver/printed circuit board connection direction: 60 °, color: green, Pin arrangement: Zigzag Pins W, Pin length [P]: 4.1 mm, number of welding pins per potential: 3, packaging type: boxed Printed circuit board terminal, Number of poles per row: 10, Item family: SPTA 16/, pitch: 10 mm, color: green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

ETIM for 1183048 Connectors (EC002643)
Feature Name
Feature Value
Height (EF000040)
42.23 mm
Number of electrical connections (EF008252)
10
Number of levels (EF002659)
1
Modular spacing connections (EF006827)
10 mm

Rated current I_n (EF008250)

76 A

Rated voltage (EF000228)

1000 V

Rated surge voltage (EF002993)

8 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Spring clamp connection

Connectable conductor cross section solid-core (EF007337)

0.75 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.75 mm²

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.75 mm²

Connectable conductor cross section multi-wired (EF007343)

10 mm²

Connection type PCB (EF006822)

Soldering connection

Material connection surface (EF006826)

Tin

Diameter connection pin (EF006823)

1.7 mm

Length pin (EF006825)

4.1 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Green

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of PCB fastening (EF008226)

Connecting contact

Type of fastening (EF002442)

Solder

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTA 16/10-CB-10,0ZM2RZBDL3INO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.