

INDUSTRIAL COMPONENT DATA

SPTA-THR 2,5/ 5-5,0 P26 1366007 PHOENIX CONTACT Printed circuit board terminal, nominal current: 32 A, nomin..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTA-THR 2,5/ 5-5,0 P26



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPTA-THR 2,5/ 5-5,0 P26
Catalog number	1366007
Category	Printed circuit board terminal
Minimum order	100 Pcs
Document ID	EO-B15628225F
Generated	2026-08-05

Product Overview

Printed circuit board terminal, nominal current: 32 A, nominal voltage (III/2): 400 V, nominal section: 4 mm², number of rows: 1, number of poles per row: 5, article family: SPTA 2.5/.. -THR, pitch: 5 mm, connection type: Push-in spring connection, mounting: THR soldering/wave soldering, conductor connection direction/printed circuit board: 45 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.6 mm, number of solder pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTA-THR 2,5/ 5-5,0 P26 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.