

INDUSTRIAL COMPONENT DATA

SPTAF 1/12-5,0-EL-EX 1071060 PHOENIX CONTACT Terminal block for printed circuit board, nominal current: 16 A..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTAF 1/12-5,0-EL-EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPTAF 1/12-5,0-EL-EX
Catalog number	1071060
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-37EB09C1AA
Generated	2026-08-04

Product Overview

Terminal block for printed circuit board, nominal current: 16 A, nominal section: 1.5 mm², number of rows: 1, number of poles per row: 12, family of articles: SPTAF 1/.. -EL-EX, pitch: 5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.6 mm, number of solder pins per potential: 2, packaging type: Tray

Printed circuit board terminal, rated current: 16 A, rated section: 1.5 mm², Number of rows: 1, Number of poles per row: 12, item family: SPTAF 1/.. -EL-EX, pitch: 5 mm, connection type: Push-in spring connection, mounting: Wave welding, conductor/printed circuit board connection direction: 45°, color: green, Pin arrangement: Double linear pin arrangement, Pin length [P]: 2.6 mm, packaging type: Tray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

ETIM for 1071060 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

12.8 mm

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

5 mm
Rated current I_n (EF008250)
16 A
Over voltage category (EF006785)
III
Pollution degree (EF006786)
2
Connection type conductor (EF006821)
Spring clamp connection
Connectable conductor cross section solid-core (EF007337)
0.2 mm²
Connectable conductor cross section fine-strand with cable end sleeve (EF007339)
0.25 mm²
Connectable conductor cross section fine-strand without cable end sleeve (EF007341)
0.2 mm²
Connectable conductor cross section multi-wired (EF007343)
1.5 mm²
Connection type PCB (EF006822)
Soldering connection
Material connection surface (EF006826)
Tin
Diameter connection pin (EF006823)
1.1 mm
Length pin (EF006825)
2.6 mm
Material insulation body (EF007543)
Other
Housing colour (EF000136)
Green
Inflammability class of insulation material according to UL94 (EF002521)
V0
Operating temperature (EF002393)
-60 °C
Type of PCB fastening (EF008226)
Connecting contact
Type of fastening (EF002442)
Solder
Type of banding (EF007011)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTAF 1/12-5,0-EL-EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.