


## INDUSTRIAL COMPONENT DATA

# SPTAF 1/15-5,0-EL 1862547 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTAF 1/15-5,0-EL



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | SPTAF 1/15-5,0-EL              |
| Catalog number  | 1862547                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 20 Pcs                         |
| Document ID     | EO-FBF41796E3                  |
| Generated       | 2026-08-03                     |

## Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 16 A, nominal voltage (III/2): 320 V, nominal section: 1.5 mm<sup>2</sup>, number of potentials: 15, number of rows: 1, number of poles per row: 15, family of articles: SPTAF 1/..-EL, pitch: 5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/printed circuit board connection direction: 45 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.6 mm, number of solder pins per potential: 2, packaging type: boxed

Printed circuit board terminal, nominal current: 16 A, rated voltage (III/2): 320 V, nominal cross section: 1.5 mm<sup>2</sup>, number of potentials: 15, number of rows: 1, number of positions per row: 15, product range: SPTAF 1/..-EL, pitch: 5 mm, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 45 °, color: green, Pin layout: Linear pinning, Solder pin [P]: 2.6 mm, number of solder pins per potential: 2, type of packaging: packed in cardboard

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

## Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family SPTAF 1/..-EL

Product line COMBICON Terminals S

Number of positions 15

Pitch 5 mm

Number of connections 15

Number of rows 1

Number of potentials 15

Pin layout Linear pinning

Solder pins per potential 2

Data management status

Article revision 01

Electrical propertiesNominal current  $I_N$  16 A

Nominal voltage  $U_N$  320 V

Rated voltage (III/3) 250 V

Rated surge voltage (III/3) 4 kV

Rated voltage (III/2) 320 V

Rated surge voltage (III/2) 4 kV

Rated voltage (II/2) 630 V

Rated surge voltage (II/2) 4 kV

Connection dataConnection technology

Nominal cross section 1.5 mm<sup>2</sup>

Conductor connection

Connection method Push-in spring connection

Conductor cross section rigid 0.2 mm<sup>2</sup> ... 1.5 mm<sup>2</sup> (When connecting and possibly adjusting a solid conductor of 1.5 mm<sup>2</sup>, the mechanical lateral forces, which can affect the terminal block, have to be absorbed by lateral support.)

0.34 mm<sup>2</sup> ... 1.5 mm<sup>2</sup> (Push-in connection)

Conductor cross section flexible 0.2 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>

Conductor cross section AWG 24 ... 16

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm<sup>2</sup> ... 0.75 mm<sup>2</sup> (Conductor connection with open terminal point)

0.5 mm<sup>2</sup> ... 0.75 mm<sup>2</sup> (Push-in connection)

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm<sup>2</sup> ... 0.75 mm<sup>2</sup> (Conductor connection with open terminal point)

0.5 mm<sup>2</sup> ... 0.75 mm<sup>2</sup> (Push-in connection)

Stripping length 8 mm

MountingMounting type Wave solder...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTAF 1/15-5,0-EL with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.