

INDUSTRIAL COMPONENT DATA

SPTAF 1/18-3,5-LL 1045306 PHOENIX CONTACT Terminal for printed circuit board, rated current: 13,5 A, rated v..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTAF 1/18-3,5-LL



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPTAF 1/18-3,5-LL
Catalog number	1045306
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-335CF5057B
Generated	2026-08-05

Product Overview

Terminal for printed circuit board, rated current: 13,5 A, rated voltage: 160 V, pitch: 3.5 mm, number of poles: 18, type of connection: spring clamp push-in, mounting: Soldering by wave direction for connection conductor/pcb: 45 °, color: green

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 160 V, nominal section: 1 mm², number of potentials: 18, number of rows: 1, number of poles per row: 18, article family: SPTAF 1/.. -LL, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.6 mm, number of solder pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTAF 1/18-3,5-LL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.