

INDUSTRIAL COMPONENT DATA

SPTAF 1/ 2-3,5-LL 1864286 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTAF 1/ 2-3,5-LL



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPTAF 1/ 2-3,5-LL
Catalog number	1864286
Category	Printed circuit board terminal
Minimum order	195 Pcs
Document ID	EO-B3421B4FF4
Generated	2026-08-03

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 160 V, nominal section: 1 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, family of articles: SPTAF 1/.. -LL, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.6 mm, number of solder pins per potential: 2, packaging type: boxed

PCB terminal block, rated current: 13.5 A, dimensioning voltage (III/2): 160 V, nominal cross-section: 1 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, product series: SPTAF 1/.. -LL, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/board connection direction: 45°, color: green, Pin layout: Linear pinning, Pin length [P]: 2.6 mm, number of solder pins per potential: 2, package type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1864286

Packing unit 195 pc

Minimum order quantity 195 pc

GTIN 4055626246260

Weight per Piece (excluding packing) 1.120 g

Custom tariff number 85369010

Country of origin PL (Poland)

Item properties

Brief article description PCB terminal block

Range of articles SPTAF 1/..-LL

Pitch 3.5 mm

Number of positions 2

Connection method Push-in spring connection

Mounting type Wave soldering

Pin layout Linear double pinning

Number of levels 1

Electrical parameters

Rated current 13.5 A

Rated insulation voltage (III/2) 160 V

Rated surge voltage (III/2) 2.5 kV

Connection capacity

Conductor cross section solid 0.2 mm² ... 0.75 mm²

Conductor cross section flexible 0.2 mm² ... 1 mm²

Conductor cross section AWG / kcmil 24 ... 18

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 0.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 0.5 mm²

Stripping length 8 mm

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics hot-dip tin-plated

Metal surface terminal point (top layer) Tin (2 - 4 µm Sn)

Metal surface soldering area (top layer) Tin (2 - 4 µm Sn)

Material data - housing

Insulating material PA

Insulating material group I

CTI according to IEC 60112 600

Flammability rating according to UL 94 V0

Dimensions for the product

Dimensional drawing

Length [l] 11 mm

Width [w] 8.5 mm

Height [h] 13.5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTAF 1/ 2-3,5-LL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.