


INDUSTRIAL COMPONENT DATA

SPTAF 1/ 5-3,5-LL 1864312 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTAF 1/ 5-3,5-LL



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPTAF 1/ 5-3,5-LL
Catalog number	1864312
Category	Printed circuit board terminal
Minimum order	90 Pcs
Document ID	EO-5DCB66A918
Generated	2026-08-05

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 160 V, nominal section: 1 mm², number of potentials: 5, number of rows: 1, number of poles per row: 5, family of articles: SPTAF 1/.. -LL, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.6 mm, number of solder pins per potential: 2, packaging type: boxed

PCB terminal block, rated current: 13.5 A, dimensioning voltage (III/2): 160 V, nominal cross-section: 1 mm², number of potentials: 5, number of rows: 1, number of poles per row: 5, product series: SPTAF 1/.. -LL, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/board connection direction: 45°, color: green, Pin layout: Linear pinning, Pin length [P]: 2.6 mm, number of solder pins per potential: 2, package type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1864312

Packing unit 90 pc

Minimum order quantity 90 pc

Note Made to Order (non-returnable)

GTIN 4055626246291

Weight per Piece (excluding packing) 2.810 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [l] 11 mm

Pitch 3.5 mm

Dimension a 14 mm

Width [w] 19 mm

Height 10.9 mm

Height [h] 13.5 mm

Solder pin [P] 2.6 mm

Pin spacing 5 mm

Hole diameter 1.1 mm

General

Range of articles SPTAF 1/..-LL

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current I_N 13.5 A

Nominal cross section 1 mm²

Solder pin surface

Stripping length 8 mm

Number of positions 5

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 0.75 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 0.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 18

Standards and Regulations

Connection in acc. with standard EN-VDE

Environmental Product Compliance

Chi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTAF 1/ 5-3,5-LL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.