

INDUSTRIAL COMPONENT DATA

SPTD 1,5/ 4-H-3,5 GY 1391704 PHOENIX CONTACT Terminal block for printed circuit board, rated current: 10 A, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTD 1,5/ 4-H-3,5 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPTD 1,5/ 4-H-3,5 GY
Catalog number	1391704
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-0BE99247E9
Generated	2026-08-02

Product Overview

Terminal block for printed circuit board, rated current: 10 A, rated voltage (III/2): 200 V, rated cross-section: 1.5 mm², number of rows: 2, number of poles per row: 4, article family: SPTD 1.5, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, driver/printed circuit board connection direction: 0°, color: gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed
Printed circuit board terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTD 1,5/ 4-H-3,5 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.