

INDUSTRIAL COMPONENT DATA

ST-17P1N8A6100S 1613540 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-17P1N8A6100S



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-17P1N8A6100S
Catalog number	1613540
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-FC01FA9447
Generated	2026-08-03

Product Overview

Device connector, front mounting

Conect. plug. to be apar. front wall, straight, for standard and SPEEDCON locking, M17, number of poles: 17, contact type: Male, Axial O-ring, Central fixing, shielded: yes, protection rating: IP67, number of poles: 17, connection type: Crimped connection, series: ST, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1242772

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1613540

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 69 (C-2-2017)

GTIN 4046356400916

Weight per Piece (excluding packing) 19.140 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Note Order information: Order crimp contacts Ø 0.6 mm separately

Type of locking for standard and SPEEDCON interlock

Direction of rotation of contact chamber numbering Standard

Coding N

Contact connection method Crimp connection

Type of contacts Pin

Number of positions 17

Contact diameter of power contacts 0.6 mm

Nominal current per power contact at 25°C 3.6 A

Pg housing screw connection none

Mounting type Central fixing

Ambient conditions

Ambient temperature -40 °C ... 125 °C

Degree of protection IP67

Specifications according to DIN EN 61984:2001

Installation height max. 3000 m

Nominal / operating voltage of power contacts 60 V

Rated surge voltage of power contacts 1.5 kV

Overvoltage category of power contacts II

Degree of pollution of power contacts 3

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss

7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 3.0EC001121ETIM 4.0EC001121ETIM 5.0EC002061ETIM 6.0EC002061

UNSPSC 6.0143172015UNSPSC 7.090143201404U...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-17P1N8A6100S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.