

INDUSTRIAL COMPONENT DATA

ST-17P1N8AH100S 1613541 PHOENIX CONTACT Device connector, rear mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-17P1N8AH100S



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-17P1N8AH100S
Catalog number	1613541
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-ACE63105C5
Generated	2026-08-02

Product Overview

Device connector, rear mounting

Connect. plug. to be apar. poster wall, straight, for standard and SPEEDCON locking, M17, number of poles: 17, contact type: Male, Axial O-ring, Central fixing, shielded: yes, protection index: IP67, number of poles: 17, connection type: Crimped connection, series: ST

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1613541

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 69 (C-2-2017)

GTIN 4046356400923

Weight per Piece (excluding packing) 29.000 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Note Order information: Order crimp contacts Ø 0.6 mm separately

Type of locking for standard and SPEEDCON interlock

Direction of rotation of contact chamber numbering Standard

Coding N

Contact connection method Crimp connection

Type of contacts Pin

Number of positions 17

Contact diameter of power contacts 0.6 mm

Nominal current per power contact at 25°C 3.6 A

Pg housing screw connection none

Mounting type Central fixing

Ambient conditions

Ambient temperature -40 °C ... 125 °C

Degree of protection IP67

Material

Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)

Insulator material PA 6.6

Gasket and O-ring material FPM

Specifications according to DIN EN 61984:2001

Installation height max. 3000 m

Nominal / operating voltage of power contacts 60 V

Rated surge voltage of power contacts 1.5 kV

Overvoltage category of power contacts II

Degree of pollution of power contacts 3

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss
7.027440103eCl@ss 8.02744010...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-17P1N8AH100S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.