

**INDUSTRIAL COMPONENT DATA**

# ST-3EP1N8AW400S000/0030/02 1622209 PHOENIX CONTACT

## Conect. enchuf. for apar. wall delant., straight, to lock..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-3EP1N8AW400S000/0030/02



|                 |                                              |
|-----------------|----------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                              |
| MPN / Reference | ST-3EP1N8AW400S000/0030/02                   |
| Catalog number  | 1622209                                      |
| Category        | Circular connector, mounting (without cable) |
| Minimum order   | 30 Pcs                                       |
| Document ID     | EO-30352C167C                                |
| Generated       | 2026-08-05                                   |

### Product Overview

Conect. enchuf. for apar. wall delant., straight, to lock standard and SPEEDCON, M17, number of poles: 3+PE, type of contact: Pin, Connection set, shielded: yes, extent of flange: 21.6 mm x 21.6 mm

Conect. plug. to be apar. front wall, straight, for standard and SPEEDCON locking, M17, number of poles: 3+PE, contact type: Male, shielded: yes, flange measurement: 21.6 mm x 21.6 mm, protection index: IP67, number of poles: 4, connection type: Crimped connection, series: ST

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Field Device Connectors (FDC)

### Additional Product Information

ETIM for 1622209 Connectors (EC003569)

Feature Name

Feature Value

With shield connection (EF002535)

Yes

Number of poles (EF001391)

4

Number of control contacts (EF012217)

4

With PE-connection (EF005600)

No

Housing material (EF001596)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Degree of protection (IP), mounted (EF007466)

IP67

Ambient temperature (EF002386)

125 °C

Operating temperature (EF002393)

-40 °C

With thread (EF003723)

Yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-3EP1N8AW400S000/0030/02 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.