

INDUSTRIAL COMPONENT DATA

ST-5EP1N8A6100S 1613548 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-5EP1N8A6100S



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-5EP1N8A6100S
Catalog number	1613548
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-33E8A3392E
Generated	2026-08-02

Product Overview

Device connector, front mounting

Conect. plug. to be apar. front wall, straight, for standard and SPEEDCON locking, M17, number of poles: 5+PE, contact type: Male, Axial O-ring, Central fixing, shielded: yes, protection index: IP67, number of poles: 6, connection type: Crimped connection, series: ST, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1242776
Device connector front mounting, straight, for standard and SPEEDCON interlock, M17, number of positions: 5+PE, contact connection type: Pin, Axial O-ring, Central fixing, shielded: yes, number of positions: 6, connection method: Crimp connection, series: ST, Alternative product in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesOrder information: Order crimp contacts Ø 1 mm separately

Safety note

Safety note WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.

- WARNING: Commission properly functioning products only. The products must be regularly inspected for damage.

Decommission defective products immediately. Replace damaged products. Repairs are not possible.

- WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical

engineering are allowed to install and operate the product.

- The products are suitable for applications in plant, controller, and electrical device engineering.
- When operating the connectors in outdoor applications, they must be separately protected against environmental influences.
- Assembled products may not be manipulated or improperly opened.
- Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
- When using the product in direct connection with third-party manufacturers, the user is responsible.
- For operating voltages > 50 V AC, conductiv...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-5EP1N8A6100S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.