

INDUSTRIAL COMPONENT DATA

ST-5ES1N8AAE00S 1618128 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-5ES1N8AAE00S



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-5ES1N8AAE00S
Catalog number	1618128
Category	Circular connector, mounting (without cable)
Minimum order	16 Pcs
Document ID	EO-8725A27ECA
Generated	2026-08-04

Product Overview

Device connector, front mounting

Connect. plug. to be apar. front wall, Swivel angle, SPEEDCON lock, M17, number of poles: 5+PE, contact type: Female, Axial O-ring, 4x Ø 3.2, shielded: yes, flange size: 25 mm x 25 mm, protection index: IP67, number of poles: 6, connection type: Crimped connection, series: ST

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1618128

Packing unit 16 pc

Note Made to Order (non-returnable)

GTIN 4046356580700

Weight per Piece (excluding packing) 96.000 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Note Order information: Order crimp contacts Ø 1 mm separately

Type of locking SPEEDCON locking

Direction of rotation of contact chamber numbering Standard

Coding N

Contact connection method Crimp connection

Type of contacts Socket

Number of positions 6

Contact diameter of power contacts 1 mm

Nominal current per power contact at 25°C 14 A

Contact diameter of signal contacts 1 mm

Pg housing screw connection none

Mounting type 4x Ø 3.2

Ambient conditions

Ambient temperature -40 °C ... 125 °C

Degree of protection IP67

Specifications according to DIN EN 61984:2001

Installation height max. 3000 m

Nominal / operating voltage of power contacts 630 V

Rated surge voltage of power contacts 6 kV

Overvoltage category of power contacts III

Degree of pollution of power contacts 3

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440312eCl@ss 8.027440312eCl@ss 9.027440312

ETIM 3.0EC001121ETIM 4.0EC001121ETIM 5.0EC002641ETIM 6.0EC002641

UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNSPSC 12.0143201404UNSPSC 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-5ES1N8AAE00S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.