


INDUSTRIAL COMPONENT DATA

ST 2,5-PCBV/ 2-G-5,2 1980488 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST 2,5-PCBV/ 2-G-5,2



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST 2,5-PCBV/ 2-G-5,2
Catalog number	1980488
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-3AECC3C351
Generated	2026-08-03

Product Overview

Feed-through header

ST-COMBI coupling, connection direction perpendicular to the printed circuit board, pitch: 5.2 mm, number of poles: 2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data

Orderkey 1980488

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 293 (C-1-2017)

GTIN 4017918972158

Weight per Piece (excluding packing) 3.110 g

Custom tariff number 85366930

Country of origin PL (Poland)

Dimensions

Length [l] 18.05 mm

Width 12.5 mm

Pitch 5.2 mm

Width [w] 12.5 mm

Height [h] 21.7 mm

Length 18.05 mm

General

Range of articles ST 2,5-PCBV/..-G

Insulating material group I

Maximum load current 24 A (with 4 mm² conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V0

Color gray

Internal cylindrical gage A3

Number of positions 2

Standards and Regulations

Connection in acc. with standard CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1980488 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5.2 mm

Modular spacing connections (EF006827)

5.2 mm

Rated current I_n (EF008250)

20 A

R...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST 2,5-PCBV/ 2-G-5,2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.