

INDUSTRIAL COMPONENT DATA

ST-OE3- 60DC/ 48DC/100 2911045 PHOENIX CONTACT

Solid-state relays

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-OE3-60DC/ 48DC/100



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-OE3-60DC/ 48DC/100
Catalog number	2911045
Category	Optocoupler
Minimum order	1 Pcs
Document ID	EO-6AA170DBE2
Generated	2026-07-29

Product Overview

Solid-state relays

Pluggable solid-state input relay, with indicator light and protection circuit protection circuit in input and output circuit, input: 48 - 60 V DC, output: 8 - 48 V DC/max. 100 mA, pluggable to base terminal blocks

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Relays**

Additional Product Information

Key Commercial Data

Orderkey 2911045

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 93 (IF-2002)

GTIN 4017918079475

Weight per Piece (excluding packing) 27.550 g

Custom tariff number 85364190

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 20.8 mm

Height 33 mm
Depth 66.5 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 60 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Input data
Nominal input voltage UN 60 V DC
Input voltage range in reference to UN 0.72 ... 1.1
Input voltage range 43.2 V DC ... 66 V DC
Switching threshold "0" signal in reference to UN ≤ 0.4
Switching threshold "1" signal in reference to UN ≥ 0.8
Typical input current at UN 9 mA
Typical response time 50 μ s
Typical turn-off time 100 μ s
Status display Yellow LED
Type of protection Reverse polarity protection
Surge protection
Protective circuit/component Polarity protection diode
Transmission frequency 300 Hz
Output data
Output voltage range 8 V DC ... 48 V DC
Limiting continuous current 100 mA
Voltage drop at max. limiting continuous current 1.2 V
Output circuit 2-conductor floating, 3-conductor ground-referenced
Type of protection Reverse polarity protection
Free running
Protective circuit/component Polarity protection diode
Damping diode
Output resistor approx. 22 k Ω (for 3-wire connection)
General
Test voltage input/output 2.5 kV AC
Mounting position a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-OE3-60DC/ 48DC/100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.