

INDUSTRIAL COMPONENT DATA

ST-OV3- 24DC/ 60DC/3 2903228 PHOENIX CONTACT

Solid-state relays

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-OV3-24DC/ 60DC/3



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-OV3-24DC/ 60DC/3
Catalog number	2903228
Category	Optocoupler
Minimum order	1 Pcs
Document ID	EO-0ABFC5DB52
Generated	2026-08-02

Product Overview

Solid-state relays

Plug-in solid-state power relay, with light indicator and protection circuit in input and output circuit, input: 24 V DC, output: 12-60 V DC/max. 3 A, pluggable to base terminal blocks.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Relays**

Additional Product Information

Key Commercial Data

Orderkey 2903228

Packing unit 10 pc

Catalog page Page 92 (IF-2005)

GTIN 4017918079000

Weight per Piece (excluding packing) 55.050 g

Custom tariff number 85364190

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 20.8 mm

Height 33 mm

Depth 66.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

Input data

Nominal input voltage UN 24 V DC

Input voltage range in reference to UN 0.8 ... 1.2

Input voltage range 19.2 V DC ... 28.8 V DC

Switching threshold "0" signal in reference to UN ≤ 0.4

Switching threshold "1" signal in reference to UN ≥ 0.8

Typical input current at UN 7 mA

Typical response time 20 μ s

Typical turn-off time 200 μ s

Transmission frequency 500 Hz

Output data

Output voltage range 12 V DC ... 60 V DC

Limiting continuous current 3 A (see derating curve)

Surge current 5 A ($t = 1$ s)

Peak offstate voltage 70 V DC (Collector-emitter reverse voltage)

Voltage drop at max. limiting continuous current 1.2 V

Output circuit 2-wire, floating

Type of protection Reverse polarity protection

Surge protection

Protective circuit/component Polarity protection diode

General

Test voltage input/output 2.5 kV AC

Mounting position any

Standards/regulations IEC 60664

IEC 60664A

DIN VDE 0110

Standards and Regulations

Standards/regulations IEC 60664

IEC 60664A

DIN VDE 0110

Environmental Product Com...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-OV3-24DC/ 60DC/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.