

INDUSTRIAL COMPONENT DATA

ST-REL7-HG220/4X21 2892465 PHOENIX CONTACT Relay connectors

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-REL7-HG220/4X21



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-REL7-HG220/4X21
Catalog number	2892465
Category	Switching relay
Minimum order	5 Pcs
Document ID	EO-A8BF0CDD20
Generated	2026-08-06

Product Overview

Relay connectors

Plug-in relay holder, equipped with Hengstler mini-round-relay, contacts (AgSnO₂+Au): Small to large powers, 4 switched contacts, input voltage 220 V DC, with light indication, pluggable into base terminal blocks

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data

Orderkey 2892465

Packing unit 5 pc

Catalog page Page 87 (IF-2002)

GTIN 4017918078713

Weight per Piece (excluding packing) 100.910 g

Custom tariff number 85364900

Country of origin DE (Germany)

Dimensions

Width 45.6 mm

Height 33 mm

Depth 66.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Coil side
Nominal input voltage UN 220 V DC
Input voltage range in reference to UN 0.8 ... 1.1
Typical input current at UN 6 mA
Typical response time 15 ms (with DC)
Typical release time 15 ms (with DC)
Protective circuit Damping diode, polarity protection Damping diode, polarity protection diode
Operating voltage display yes
Power dissipation for nominal condition 1.32 W
Contact side
Contact type Single contact, 4-PDT
Type of switch contact Single contact
Contact material AgCdO, hard gold-plated
Maximum switching voltage 250 V AC/DC
Maximum inrush current 6 A
Limiting continuous current 6 A
Interrupting rating (ohmic load) max. 120 W (at 24 V DC)
180 W (at 48 V DC)
105 W (at 60 V DC)
60 W (at 110 V DC)
90 W (at 220 V DC)
1250 VA (for 250 V AC)
General
Test voltage relay winding/relay contact 2 kV AC (50 Hz, 1 min.)
Test voltage PDT/PDT 2 kV AC (50 Hz, 1 min.)
Operating mode 100% operating factor
Mechanical service life approx. 107cycles
Net weight (SAP) 100.91 g
Standards and Regulations
Standards/regulations IEC 60664
IEC 60664A
DIN VDE 0110
DIN VDE 0109-11, draft
DIN VDE 0160 (in relevant....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-REL7-HG220/4X21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.