

INDUSTRIAL COMPONENT DATA

ST-SILED 24-UK 2MA 3048742 PHOENIX CONTACT Fuse plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-SILED 24-UK 2MA



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-SILED 24-UK 2MA
Catalog number	3048742
Category	Component plug terminal block
Minimum order	50 Pcs
Document ID	EO-20931CA223
Generated	2026-08-01

Product Overview

Fuse plug
 Fuse head

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3048742
 Packing unit 50 pc
 Minimum order quantity 50 pc
 Note Made to Order (non-returnable)
 GTIN 4046356134545
 Weight per Piece (excluding packing) 5.960 g
 Custom tariff number 85369095
 Country of origin PL (Poland)

General

Note If the fuse is defective, the downstream circuit is not off load
 Flammability rating according to UL 94 V0
 Relative insulation material temperature index (Elec., UL 746 B) 130 °C
 Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
 Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Standards and Regulations
Flammability rating according to UL 94 V0
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-SILED 24-UK 2MA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.