

INDUSTRIAL COMPONENT DATA**PZ 1,5/S/2 3212918 PHOENIX CONTACT Strain relief**

Brand: PHOENIX CONTACT | Manufacturer Part Number: PZ 1,5/S/2



Manufacturer	PHOENIX CONTACT
MPN / Reference	PZ 1,5/S/2
Catalog number	3212918
Category	Installation clamp for meters
Minimum order	50 Pcs
Document ID	EO-07DB812843
Generated	2026-08-03

Product Overview

Strain relief

Traction Compensator, Length: 44.5 mm, Width: 6.8 mm, Number of Poles: 2, Color: Black

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **PHOENIX CONTACT > Modular TBs****Additional Product Information**

Key Commercial Data

Orderkey 3212918

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 362 (C-1-2017)

GTIN 4046356566056

Weight per Piece (excluding packing) 0.700 g

Custom tariff number 39269097

Country of origin PL (Poland)

General

Number of positions 2

Color black

Material PA-GF

Flammability rating according to UL 94 V0

Dimensions

Width 6.8 mm

Length 44.5 mm

General

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C

Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Standards and Regulations

Flammability rating according to UL 94 V0

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protect...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PZ 1,5/S/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.