

INDUSTRIAL COMPONENT DATA

STTB 2,5-R1K/O-U 1032740 PHOENIX CONTACT Double-level spring-cage terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: STTB 2,5-R1K/O-U



Manufacturer	PHOENIX CONTACT
MPN / Reference	STTB 2,5-R1K/O-U
Catalog number	1032740
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-BE8071A94D
Generated	2026-08-02

Product Overview

Double-level spring-cage terminal block

Double-deck spring terminal block, nominal voltage: 500 V, nominal current: 22 A, connection type: Spring connection, 1st and 2nd floor, Sizing cross-section: 2.5 mm², cross-section: 0.08 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 1032740

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4055626537610

Weight per Piece (excluding packing) 22.220 g

Custom tariff number 85369010

Country of origin PL (Poland)

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141121eCl@ss 4.127141121eCl@ss 5.027141120eCl@ss 5.127141120eCl@ss 6.027141100eCl@ss
7.027141120eCl@ss 8.027141120eCl@ss 9.027141120

ETIM 2.0EC000897ETIM 3.0EC000897ETIM 4.0EC000897ETIM 5.0EC000897ETIM 6.0EC000897

UNSPSC 6.0130211811UNSPSC 7.090139121410UNSPSC 1139121410UNSPSC 12.0139121410UNSPSC
13.239121410

ETIM for 1032740 Terminal blocks (EC000897)

Feature Name**Feature Value**

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.08 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.14 mm²

Connectable conductor cross section solid-core (EF007337)

0.08 mm²

Rated current I_n (EF008250)

22 A

Rated voltage (EF000228)

500 V

Type of electrical connection 1 (EF002526)

Spring clamp connection

Type of electrical connection 2 (EF002527)

Spring clamp connection

Number of levels (EF002659)

2

Number of clamp positions per level (EF002660)

2

Suitable for conductor material (EF012572)

Aluminium/copper

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

Material insulation body (EF007543)

Other

Inflammabi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STTB 2,5-R1K/O-U with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.