

INDUSTRIAL COMPONENT DATA

SUBCON 15 HD/M-SH 5604602 PHOENIX CONTACT D-SUB bus connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SUBCON 15 HD/M-SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SUBCON 15 HD/M-SH
Catalog number	5604602
Category	D-Sub connector
Minimum order	1 Pcs
Document ID	EO-1F4F975415
Generated	2026-08-05

Product Overview

D-SUB bus connector

D-SUB plug, 15 poles, two 35° cable entries, universal type for all systems, pole diagram: 1, 2, 3, ..., 14, 15 on screw connection terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Safety**

Additional Product Information

Key Commercial Data

Orderkey 5604602

Packing unit 1 pc

GTIN 4046356685214

Weight per Piece (excluding packing) 72.500 g

Custom tariff number 85366990

Country of origin US (United States)

Dimensions

Max. cable diameter 12.7 mm

Min. cable diameter 4 mm

Width 16 mm

Height 49.8 mm

Length 61 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 75 °C

Ambient temperature (storage/transport) -25 °C ... 80 °C

Altitude 5000 m (For restrictions see manufacturer's declaration)

Degree of protection IP20

General

Nominal voltage UN 48 V AC/DC

Nominal current IN 1 A

Signal Point-to-point

Insertion/withdrawal cycles > 50

SUBCON fixing screws 4-40 UNC

Tightening torque 0.4 Nm

Housing material ABS, metal-plated

Pin assignment All connections are 1:1 on the screw terminal block

Connection data

Connection D-SUB connection

Number of positions 15

Connection method High density D-SUB pin strip

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

ClassificationseCl@ss 4.027140816eCl@ss 4.127140816eCl@ss 5.027143424eCl@ss 5.127143400eCl@ss 6.027143400eCl@ss
7.027440302eCl@ss 8.027440302eCl@ss 9.027440302

ETIM 3.0EC001132ETIM 4.0EC001132ETIM 5.0EC001132ETIM 6.0EC001132

UNSPSC 6.013021180UNSPSC 7.090139121402UNSPSC 1139121402UNSPSC 12.0139121402UNSPSC
13.239121522

ETIM for 5604602 Data networking products (EC001132)

Feature Name

Feat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend PHOENIX CONTACT / SUBCON 15 HD/M-SH with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.**GLOBAL OFFICES**Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, DubaiCatalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.