


INDUSTRIAL COMPONENT DATA

AB-SK-D TOP INSULATED 3062087 PHOENIX CONTACT

Support bracket

Brand: PHOENIX CONTACT | Manufacturer Part Number: AB-SK-D TOP INSULATED



Manufacturer	PHOENIX CONTACT
MPN / Reference	AB-SK-D TOP INSULATED
Catalog number	3062087
Category	Busbar support
Minimum order	10 Pcs
Document ID	EO-A22F292556
Generated	2026-08-03

Product Overview

Support bracket

Stand, Busbar support, place every 20 cm, length: 155.8 mm, width: 5.2 mm, number of poles: 2, color: gray, mounting class: Rail mounting

Support block, Busbar holder, to be fixed every 20 cm, width: 5.2 mm, height: 155.8 mm, number of poles: 2, colour: grey, mounting type: DIN rail mounting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data

Orderkey 3062087

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 617 (C-3-2017)

GTIN 4046356591850

Weight per Piece (excluding packing) 23.140 g

Custom tariff number 85389099

Country of origin CN (China)

Dimensions

Length (b) 155.8 mm

Width (a) 5.2 mm

General

Color gray

Flammability rating according to UL 94 V0

Material PA

Insulating material PA

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.023150301eCl@ss 4.123150301eCl@ss 5.027141143eCl@ss 5.127141100eCl@ss 6.027409200eCl@ss
7.027409221eCl@ss 8.027409221eCl@ss 9.027400607

ETIM 2.0EC000761ETIM 3.0EC000761ETIM 4.0EC002270ETIM 5.0EC002270ETIM 6.0EC001166

UNSPSC 6.0130212109UNSPSC 7.090139121708UNSPSC 1139121708UNSPSC 12.0139121708UNSPSC
13.239121708

ETIM for 3062087 Power distribution systems (EC001166)

Feature Name

Feature Value

Number of poles (EF001391)

2

Max. rated current (EF007926)

0 A

Busbar distance (EF002638)

65 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AB-SK-D TOP INSULATED with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.