

**INDUSTRIAL COMPONENT DATA**

# AB-SK TOP INSULATED 3062074 PHOENIX CONTACT

## Support bracket

Brand: PHOENIX CONTACT | Manufacturer Part Number: AB-SK TOP INSULATED



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | PHOENIX CONTACT     |
| MPN / Reference | AB-SK TOP INSULATED |
| Catalog number  | 3062074             |
| Category        | Busbar support      |
| Minimum order   | 10 Pcs              |
| Document ID     | EO-410035682A       |
| Generated       | 2026-07-31          |

### Product Overview

Support bracket

Stand, Busbar support, place every 20 cm, length: 102.4 mm, width: 5.2 mm, number of poles: 2, color: gray, mounting class: Rail mounting

Support bracket, Bracket for busbars, set every 20 cm, width: 5.2 mm, height: 102.4 mm, number of positions: 2, color: gray, mounting type: DIN rail mounting

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; CABINET add-on

### Additional Product Information

Technical dataNotesAssembly note isolated from NS 35

Product propertiesProduct type Support bracket

Number of positions 2

Data management status

Article revision 00

Electrical propertiesNominal current IN 0 A

DimensionsWidth 5.2 mm

Height 102.4 mm

Depth on NS 35/7,5 63.2 mm

Depth on NS 35/15 70.7 mm

Material specificationsColor gray (RAL 7042)

Material PA

Insulating material PA

Static insulating material application in cold -60 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Environmental and real-life conditions Ambient conditions

Ambient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (storage/transport) 30 % ... 70 %

Mounting Mounting type DIN rail mounting

ETIM for 3062074 Power distribution systems (EC001166)

Feature Name

Feature Value

Number of poles (EF001391)

2

Max. rated current (EF007926)

0 A

Busbar distance (EF002638)

65 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AB-SK TOP INSULATED with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.