

INDUSTRIAL COMPONENT DATA

VAL-MS 320/3+0-FM 2920243 PHOENIX CONTACT Type 2 surge arrester

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-MS 320/3+0-FM



Manufacturer	PHOENIX CONTACT
MPN / Reference	VAL-MS 320/3+0-FM
Catalog number	2920243
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-33777E3FE1
Generated	2026-08-04

Product Overview

Type 2 surge arrester

Surge arrester for 4-conductor power supply systems (L1, L2, L3, PEN), consisting of base element with remote indication contact and plug-in protections, for installation on NS 35.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2920243

Packing unit 1 pc

Catalog page Page 53 (C-4-2017)

GTIN 4046356157087

Weight per Piece (excluding packing) 352.700 g

Custom tariff number 85363010

Country of origin DE (Germany)

Dimensions

Height 98.7 mm

Width 53.4 mm

Depth 65.7 mm (incl. DIN rail 7.5 mm)

Horizontal pitch 3 Div.

Ambient conditions

Degree of protection IP20 (only when all terminal points are used)

Ambient temperature (operation) -40 °C ... 80 °C

Ambient temperature (storage/transport) -40 °C ... 80 °C

Altitude $\leq$ 2000 m (amsl (above mean sea level))

Permissible humidity (operation) 5 % ... 95 %

Shock (operation) 25g (Half-sine / 11 ms / $3x \pm X, \pm Y, \pm Z$)

Vibration (operation) 5g (10 ... 500 Hz / 2.5 h / X, Y, Z)

General

IEC test classification II

T2

EN type T2

IEC power supply system TN-C

Mode of protection L-PEN

Mounting type DIN rail: 35 mm

Color jet black RAL 9005

Housing material PA 6.6

PBT

Degree of pollution 2

Flammability rating according to UL 94 V-0

Type DIN rail module, two-section, divisible

Number of positions 3

Surge protection fault message Optical, remote indicator contact

Protective circuit

Nominal voltage UN 240/415 V AC (TN-C)

Nominal frequency f_N 50 Hz (60 Hz)

Maximum continuous voltage UC 335 V AC

Rated load current IL 80 A

Residual current IPE $\leq$ 1.35 mA

Standby power consumption PC $\leq$ 450 mVA

Nominal discharge current $I_n(8/20)$ μ s 20 kA

Maximum discharge current $I_{max}(8/20)$ μ s 40 kA

Short-circuit current rating ISCCR 25 kA

Voltage protection level Up $\leq$ 1.5 kV....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-MS 320/3+0-FM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.