

INDUSTRIAL COMPONENT DATA

VAL-MS 580/3+0-FM 2920447 PHOENIX CONTACT Type 2 surge arrester

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-MS 580/3+0-FM



Manufacturer	PHOENIX CONTACT
MPN / Reference	VAL-MS 580/3+0-FM
Catalog number	2920447
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-DA9D1CD596
Generated	2026-08-04

Product Overview

Type 2 surge arrester

Surge arrester for 4-conductor power supply systems (L1, L2, L3, PEN), consisting of base element with remote indication contact and plug-in protections, for installation on NS 35.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2920447

Packing unit 1 pc

Catalog page Page 41 (C-6-2015)

GTIN 4046356163569

Weight per Piece (excluding packing) 386.100 g

Custom tariff number 85363030

Country of origin DE (Germany)

Dimensions

Height 98.7 mm

Width 53.4 mm

Depth 65.7 mm (incl. DIN rail 7.5 mm)

Horizontal pitch 3 Div.

Ambient conditions

Degree of protection IP20 (only when all terminal points are used)

Ambient temperature (operation) -40 °C ... 80 °C

Ambient temperature (storage/transport) -40 °C ... 80 °C

Altitude ≤ 2000 m (amsl (above mean sea level))

Permissible humidity (operation) 5 % ... 95 %

Shock (operation) 25g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)

Vibration (operation) 5g (10 ... 500 Hz / 2.5 h / X, Y, Z)

General

IEC test classification II

T2

EN type T2

IEC power supply system TN-C

IT

Mode of protection L-PE

L-PEN

Mounting type DIN rail: 35 mm

Color jet black RAL 9005

Housing material PA 6.6

PBT

Degree of pollution 2

Distance between live and grounded parts 5 mm

Flammability rating according to UL 94 V-0

Type DIN rail module, two-section, divisible

Number of positions 3

Surge protection fault message Optical, remote indicator contact

Additional descriptions

Note For use in all low-voltage systems between L-PEN.

Only for use in IT systems between L-PE if the bodies of the equipment in the low-voltage system are connected to the grounding system of the transformer station. (common grounding of the HV transformer station and the bodies of the LV consumer's installation. RE=...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-MS 580/3+0-FM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.